## UTHLITY TRAILERS

## 3 SK HITRA LICHT ANGLE TOP

**AXLE** 3500# Quality Dexter Axle Idler

**COUPLER** 2" Durable Atwood A-Frame Style CROSS MEMBERS 2" x 2" x 1/8" Angle Iron

FENDERS 8" x 28" Rounded Steel

FLOOR Pressure Treated 2x8 Pine Wood Planks Expanded Metal may be substituted at

no additional charge.

FRAME 2" x 2" x 1/8" Angle Iron

JACK Not Standard on this Trailer (See Options)

LIGHTS All boxed-in LED lights.

PAINT Cleaned and prepared metal is primed with

High Performance Primer and then given two coats of quality oil based, AUTOMOTIVE GRADE, anti-corrosion paint for an extra durable high

gloss finish that lasts.

PLUG 4-way plug with protective loom and

security brackets

SAFETY CHAINS 1/4" x 27" with S-Hook.

5200# capacity rating per chain.

STAKE POCKETS 2" x 4" Pockets. Two per side

TAIL GATE 1-1/2" x 1-1/2" Square Tubing

with expanded metal. Rear gate is

3 ft tall with upright supports and two durable latches. Folds down for easy ramp loading and is removable.

**TONGUE** Wrapped Tongue Complete. 3" x 2" x 3/16" Angle Iron

TOP RAIL 2" x 2" x 1/8" Angle Iron UPRIGHTS 2"x 2" x 1/8" Angle Iron

TIRES ST175/13



IS ALWAYS A WELCOME IDEA

Whatever the need, Stagecoach engineers will design and plan the perfect custom trailer solution











