TANDEM AXLE

BUMPER PULL

PIPF TOP

MULTI-PURPOSE WE WIND THE WIND WIND THE PROPERTY OF THE PROPE

AXLE Two 3500# Quality Dexter Axle Idler

COUPLER 2" Atwood A-Frame Style

CROSS MEMBERS 3" x 2" x 3/16" Angle Iron

FENDERS Straight

FLOOR Pressure Treated 2x8 Pine Wood Planks Expanded Metal may be substituted at no additional charge.

FRAME 3" x 2" x 3/16" Angle Iron

JACK 2000# Top Wind. Set Back Jack

LIGHTS All boxed-in LED lights.

PAINT Cleaned and prepared metal is primed with High Performance Primer and then given two coats of quality oil based, AUTOMOTIVE GRADE, anti-corrosion paint for an extra durable high

gloss finish that lasts.

PLUG 4-way plug with protective loom and

security brackets

SAFETY CHAINS 1/4" x 27" with S-Hook.

5200# capacity rating per chain.

STAKE POCKETS 2" x 4" Pockets. Two per side

REAR 2" x 2" x 1/8" board holders & 1"x1"x1/4" ramp lip

TONGUE Wrapped Tongue Complete. 4" Channel.

The 4" Channel Iron provides outstanding weight distribution and stronger support for wider trailers.

TOP RAIL 2 3/8" Pipe Top

UPRIGHTS 2"x 2" x 1/8" Angle Iron

TIRES ST205/75

WHEELS 15" Silver or White Mod Wheels.

5 on 5 Bolt Pattern

"DOC HOLLIDAY" STANDARD SIZES 83" x 14' 83" x 18' 83" x 16' 83" x 20'

Whatever the need, Stagecoach

engineers will design and plan the

perfect custom trailer solution

7K GENERAL DUTY

PIPE TOP UTILITY XTRA WIDE









STAGECOACH TRAILERS

