TANDEM AXLE

BUMPER PULL

STEEL FLOOR

CAR HAULER

"McCLINTOCK"

STANDARD SIZES

77" x 16'
83" x 16'
83" x 18'

CUSTOM

83" x 20'

IS ALWAYS A WELCOME IDEA

Whatever the need, Stagecoach engineers will design and plan the perfect custom trailer solution

AXLE 3500# Quality Dexter Axle Idler

AXLE 3500# Quality DEXTER Axle with Brake

COUPLER 2" Bulldog Style Coupler

CROSS MEMBERS 3" x 2" x 3/16" Angle Iron

FENDERS Straight Fenders

FLOOR 1/8" Steel Floor with Four

Flush Mount D Rings

FRAME 5" Channel

JACK 2000# Top Wind. Set Back Jack

LIGHTS All boxed-in LED lights.

PAINT Cleaned and prepared metal is primed with

High Performance Primer and then given two coats of quality oil based, AUTOMOTIVE GRADE, anti-corrosion paint for an extra durable high

gloss finish that lasts.

PLUG 7-way plug with protective loom and

security brackets

SAFETY CHAINS 5000# capacity rating per chain.

STAKE POCKETS 2" x 4" Pockets. Two per side

RAMPS 1.5" Square Tubing. 5' length with slide in pockets

TONGUE Wrapped Tongue Complete. 5" Channel.

The 5" Channel Iron provides outstanding weight distribution and stronger support for wider trailers.

FRONT RAIL 2 3/8" Pipe

UPRIGHTS 3" x 2" x 3/16" Angle Iron

TIRES ST205/75

WHIELS 15" Silver or White Mod Wheels.

5 Hole

STAGECOACH TRAILERS









